



IP 10 SUB [CodeNr. 13305]

The Solton IP 10 Sub is a single 10" direct small sized subwoofer. It has been designed to add high-output loudspeaker systems in various installed applications. The IP 10 Sub features a long-excursion, 10" ,2" (50mm) voice coil LF transducer, and a low distortion port design in a compact reflex enclosure made of 15 mm plywood. The integrated Handle makes this Sub also perfect for mobile use. The wall mount accessories complete this Sub to a perfect small size allrounder for installation on the ground or on walls. Two speakon connectors (NL4) are mounted at the rear side of the enclosure for signal input (input), signal link (PARALLEL). The IP 10 Sub has many features that make it a versatile subwoofer system.

Specification

Key features

- > 1x 10" , 2" (50mm) voice coil LF Transducer
- > Wallmount accessories available
- > Passive subwoofer operation
- > Compact design
- > Integrated Handle for Easy Portability

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs

Recommended with

- > Tops:
IP 5 CX, 5CX, IP 8
- > Amps:
QX 700, DX43

For more informations please check our website or contact us.

Loudspeaker Type	Single10", bass-reflex, subwoofer
Frequency Range (-10dB)	40 Hz - 300 Hz
Frequency Response (+- 3dB)	50 Hz - 250 Hz
Coverage Pattern	Omni
Power Handling	300 W continuous, 1200 W peak
System Sensitivity (1w/1m)	97 dB
Maximum SPL (Calculated at 1m)	122 dB continuous, 128 dB peak
HF Driver	n/a
LF Driver	10", 2" voice coil speaker
Nominal Impedance	8 ohms
Crossover	active by DSP
Protection	Limiter by DSP
Active Tuning / Features	n/a
Enclosure	15 mm Birch plywood
Finish	Black textured paint
Fittings	Handle, Wall mount optional
Protective Grille	Black perforated steel with acoustic transparent foam backing
Connectors	2x NL 4, 1+/- IN
Dimensions mm (WxHxD)	298 x 402 x 400
Weight	12 kg