



## 5 CX [CodeNr. 12109]

5 CX is an ultra-compact coaxial two-way high performance loudspeaker for applications requiring good acoustic and power handling characteristics, and minimum visual impact. It provides wide but precise coverage distortion free up to level of 118 dB.

Multiple mounting options (U-bracket included in delivery as standard) and connection possibilities make the 5 CX a very efficient sound reinforcement tool for a wide range of near field applications in fix installed and mobile use.

Also available in white. [CodeNr. 12101]

### Specification

Loudspeaker Type	Two-way, Passive, 5" coaxial, monitor angle 45°
Frequency Range (-10db)	80 Hz - 20 kHz
Frequency Response (± 3dB)	90 Hz - 18 kHz
Coverage Pattern	90° Coaxial
Power Handling	120 W continuous, 240 W program
System sensitivity (1w/1m)	92 dB
Maximum SPL (Calculated at 1m)	118 dB peak
HF Driver	1"
LF Driver	5" 1,5" voice coil, weather resistant
Nominal Impedance	8 ohms
Crossover	2,2 kHz
Protection	n/a
Active Tunings / Features	n/a
Enclosure	Multi-angle, 10mm plywood
Finish	Black textured paint
Fittings	1 x Flange 3/8" pole mount socket, U Bracket
Protective Grill	Black perforated steel with acoustic transparent foam
Connectors	2 x NL 4, Terminal strip
Dimensions mm (WxHxD)	185 x 185 x 170
Weight	3,2 kg

### Key features

- > High resolution coaxial 2-way design with 1" HF driver
- > Ultra Compact design
- > 90° Coaxial
- > Passive fullrange operation
- > U-bracket included in delivery (as standard)
- > 3/8" Pole mount socket
- > Monitor angle (45°)
- > Weight only 3,2 kg

### Application

- > Front Fill Cinema / Theater
- > FX Speakers
- > Nearfield Monitors
- > Convention Centers
- > Bars and restaurants
- > Nightclubs
- > Studio Monitors
- > Broadcast Monitors
- > Mobile Conference

### Recommended with

- > Subs:  
TA 12 Sub, SUB 315, SB 15 N
- > Amps:  
DX43
- > Controller:  
DSP 206 N



Druckfehler / Irrtümer vorbehalten / Limited liability on contents

SOLTON Acoustic GmbH & Co. KG

Oberer Mühlweg 6 | Pocking | GERMANY | T +49 8531 913880

mail@solton.com | www.solton.com