



aart T 215 A [CodeNr. 13109]

AART T-215 A – High-Power Full-Range System for Large-Scale Applications

The AART T-215 A is a high-performance full-range speaker engineered for powerful main system applications in large venues and outdoor environments. Designed to deliver exceptional output and clarity, it is the ideal solution when maximum sound pressure and coverage are required. Equipped with two 15" neodymium woofers featuring 3" voice coils and a dedicated high-frequency neodymium driver with a 3" voice coil, the system ensures a well-balanced, dynamic sound with impressive low-end punch and detailed highs. The bass-reflex design further enhances low-frequency performance, providing the depth and impact essential for demanding live applications. Powered by a 1400-watt Class-D amplifier module, the AART T-215 A delivers outstanding efficiency and headroom. An advanced DSP system with integrated protection ensures reliable operation, while FIR filtering enables precise sound tuning and improved overall clarity. Despite its powerful performance, the speaker features a lightweight and compact enclosure, making it practical for transport and setup. Compared to conventional 15" full-range systems, the AART T-215 A achieves an impressive increase of 6–8 dB in sound pressure level, delivering significantly greater output and presence. Thanks to its dual 15" configuration and dedicated high-frequency driver, it is perfectly suited for large indoor spaces as well as outdoor events. The system can also be combined with subwoofers in stacked configurations to create a powerful, full-range setup capable of delivering an immersive and impactful audience experience. Built for Impact With its combination of power, precision, and efficiency, the AART T-215 A is the perfect choice for professionals seeking a reliable and high-output solution for demanding live sound environments.

Key features

- > High-class performance in a compact design
- > Class D bi-amped power module
- > 4 DSP presets, FIR
- > Dual-band limiter
- > M8 inserts for flexible mounting options

Application

- > Portable sound reinforcement
- > Installation
- > Live Music
- > Bars and restaurants
- > Nightclubs
- > Corporate AV events and conferences

Recommended with

- > Subs:
SUB 18 BPA

For more informations please check our webside or contact us.

Specification

Loudspeaker Type	Self-powered, two-way bi-amped
Frequency Range (-10dB)	45 Hz - 20 kHz
Frequency Response (+- 3dB)	55 Hz - 18 kHz
Coverage Pattern	H 90° x V 70° nominal
Power Handling	1400 W continuous, 5600 W peak
HF Driver	3" voice coil, neodym compression driver
LF Driver	2x 15", neodym speaker aaCRAAFT
Crossover	Active / DSP
Protection	Limiter, over voltage protection, PFC
Active Tuning / Features	Volume, DSP, Power Switch
Enclosure	Birch plywood
Finish	Black polyurea coating
Fittings	5x M8 inserts, 2x handle
Protective Grille	Powder coated, black perforated steel with acoustic cloth inside
Connectors	XLR in/out, Power in
Dimensions mm (WxHxD)	410 x 940 x 450
Weight	33 kg